

# flexifoam

## PRODUCT DATA SHEET

PRODUCT NAME	<b>Flexifoam Block ZF/PF/RF AO (+ Angle - Round - Double angle - A1/2R)</b>
SIZE	98x68x26 mm (tolerance $\pm 2$ mm)
GRIT SIZES	#36 #46 #54 #60 #80 #100 #120 #150 #180 #220
GRIT TYPES	Brown Aluminium Oxide All the grits used on all our products are to F.E.P.A. standards The grits are not harmful and do not give off any toxic vapours or smells. The products can be used wet or dry, and the grit cleaned by rinsing off the residue particles in clean water. It is recommended that when using these products a facemask and eye protection be worn to guard against airborne particles from being worked upon.
FOAM	Grey P.U. open cell of medium/hard density. The material is non-toxic in its solid form. Do not place under direct flame or on open fire as the foam gives off dangerous vapours.
ADHESIVE	Highly flexible rubber based adhesive The adhesive bond between the grit and the foam is a highly flexible rubber based film that is non-toxic in its cured form.
COATED	4 sides
COMPOSITION / INFORMATION ON INGREDIENTS	It is a fact that due to the composition of the materials used in the make up of these products that the physical feel of the items will vary with extreme changes in the ambient temperature or storage conditions. However, this will not detract from the performance of the products.

