

# flexifoam

## PRODUCT DATA SHEET

|  |  |
|--|--|
| PRODUCT NAME                             | <b>Flexifoam Pad ZF1S(P), ZF2S, SC/AO</b>  |
| SIZE                                     | 140x115x5 mm & 120x98x5 mm (tolerance $\pm 2$ mm)  |
| GRIT SIZES                               | #36 #46 #54 #60 #80 #100 #120 #150 #180 #220 #280 #320 #400  |
| GRIT TYPES                               | Silicon Carbide or Aluminium Oxide<br>All the grits used on all our products are to F.E.P.A. standards<br>The grits are not harmful and do not give off any toxic vapours or smells.<br>The products can be used wet or dry, and the grit cleaned by rinsing off the residue particles in clean water.<br>It is recommended that when using these products a facemask and eye protection be worn to guard against airborne particles from being worked upon. |
| FOAM                                     | Grey P.U. open cell of medium density<br>The material is non-toxic in its solid form. Do not place under direct flame or on open fire as the foam gives off dangerous vapours.   |
| ADHESIVE                                 | Nitrile Adhesive or Highly flexible rubber based adhesive<br>The adhesive bond between the grit and the foam is a highly flexible nitrile adhesive or highly flexible rubber based adhesive that is non-toxic in its cured form. Should the products be handled in the first few days after manufacture, it could give off a strong smell. This smell is neither toxic nor harmful in any way and should dissipate quite quickly                             |
| COATED                                   | One or both sides  |
| COMPOSITION / INFORMATION ON INGREDIENTS | It is a fact that due to the composition of the materials used in the make up of these products that the physical feel of the items will vary with extreme changes in the ambient temperature or storage conditions. However, this will not detract from the performance of the products.  |

